








EI-57

AC-AC ADAPTERS

Last Update: 2005-4-20

MODEL	OUTPUT		SAFETY							
	Volt Vac	Amp	CB Report		UL	CE Countries		United Kingdom		SAA
			IEC 60950	IEC 61558	 UL 1310	 EN 60950	 EN 61558	 BS EN 60950	 BS EN 61558	
TEAD-57-053000V1/VB	5.00	3.00A		*			*		*	
TEAD-57-06xxxx U/V/V1/VB/A	6.00	2.00A,2.50 A	*	*	*	*	*	*	*	*
TEAD-57-063000 U/V1/A	6.00	3.00A		*	*		*		*	*
TEAD-57-072000 V/V1/VB/A	7.00	2.00A	*	*		*	*	*	*	*
TEAD-57-072500 V1/VB/A/U	7.00	2.50A		*	*		*		*	*
TEAD-57-091500 V/V1/VB/A	9.00	1.50A	*	*		*	*	*	*	*
TEAD-57-092000 U/V/V1/VB/A	9.00	2.00A	*	*	*	*	*	*	*	*
TEAD-57-101500 V/V1/VB/A	10.00	1.50A	*	*		*	*	*	*	*
TEAD-57-102000 U/V/V1/VB/A	10.00	2.00A	*	*	*	*	*	*	*	*
TEAD-57-12xxxx U/V/V1/VB/A	12.00	1.50A,1.60 A	*	*	*	*	*	*	*	*
TEAD-57-121000U5	12.00	1.0A			*					
TEAD-57-121700 U	12.00	1.70A			*					

TEAD-57-121800 U/V/V1/VB/A	12.00	1.80A	*	*	*	*	*	*	*	*
TEAD-57-131000 U/V/V1/VB	13.50	1.00A	*	*	*	*	*	*	*	*
TEAD-57-131200 V/V1/VB/A	13.50	1.20A	*	*	*	*	*	*	*	*
TEAD-57-131300 U/V/V1/VB/A	13.50	1.30A	*	*	*	*	*	*	*	*
TEAD-57-131400 U	13.50	.40A			*					
TEAD-57-131500 U/V/V1/VB/A	13.50	1.50A	*	*	*	*	*	*	*	*
TEAD-57-13xxxx U	13.50	1.60A,1.70 A			*					
TEAD-57-131800 U	13.50	1.80A			*					
TEAD-57-141000 V/V1/VB/A	14.00	1.00A	*	*	*	*	*	*	*	*
TEAD-57-141200 U/V1/V/VB	14.00	1.20A	*	*	*	*	*	*	*	*
TEAD-57-141300 U	14.00	1.30A								
TEAD-57-145150 U	14.50	1.50A			*					
TEAD-57-151000 V/V1/VB/A	15.00	1.00A	*	*	*	*	*	*	*	*
TEAD-57-151200 U/A	15.00	1.20A			*					*
TEAD-57-151500 U/V/V1/VB/A	15.00	1.50A	*	*	*	*	*	*	*	*
TEAD-57-152000 U	15.00	2.00A								
TEAD-57-16xxxx U	16.00	1.00A,1.20 A,1.50A			*					
TEAD-57-171000 U	17.00	1.00A			*					
TEAD-57-180800 V/V1/VB/A	18.00	0.80A	*	*	*	*	*	*	*	*
TEAD-57-18xxxx U/V/V1/VB/A	18.00	1.00A ,1.20A	*	*	*	*	*	*	*	*

TEAD-57-181500 U	18.00	1.50A			*					
TEAD-57-200800 V/V1/VB/A	20.00	0.80A	*	*		*	*	*	*	*
TEAD-57-201000 U/V/V1/VB/A	20.00	1.00A	*	*	*	*	*	*	*	*
TEAD-57-201200 V/V1/VB/A	20.00	1.20A	*	*		*	*	*	*	*
TEAD-57-240600 V/V1/VB/A	24.00	0.60A	*	*		*	*	*	*	*
TEAD-57-240750 U	24.00	0.75A			*					
TEAD-57-240800 V/V1/VB/A	24.00	0.80A	*	*		*	*	*	*	*
TEAD-57-241000 U	24.00	1.00A			*					
TEAD-57-121500 UT	12.00	1.50A			*					

UL FILE NO: E159614

CB:JPTUV-001960,DE 2-001833,DE 2003693,JPTUV-001960-ML

BSI Certificate NO: T 9956489,TA2057502

TUV Certificate NO: S12057476,S19754150

SAA Certificate NO:15826 Q01324

